


# Florida Beach Tarball 11 on Rxi-5HT (15 m x 0.25 mm x 0.10 µm)

Peaks	tr (sec)
1. C10	125.0
2. C20	468.9
3. C30	694.3
4. C40	857.6
5. C50	983.6



**Column** Rxi-5HT, 15 m, 0.25 mm ID, 0.10 µm (cat.# 13905)  
**Sample** Tarball 11 - Florida Gulf beach  
**Diluent:** Carbon disulfide  
**Injection**  
Inj. Vol.: 1 µL split (split ratio 10:1)  
Liner: Premium 4 mm Precision liner w/wool (cat.# 23305)  
Inj. Temp.: 275 °C  
Split Vent Flow Rate: 17.5 mL/min  
**Oven**  
Oven Temp.: 40 °C (hold 0.1 min) to 400 °C at 19.6 °C/min (hold 1.53 min)  
**Carrier Gas** Hz, constant flow  
Flow Rate: 1.75 mL/min  
**Detector** FID @ 420 °C  
Constant Column + Constant Make-up: 50 mL/min  
Make-up Gas Type: N<sub>2</sub>  
Hydrogen flow: 40 mL/min  
Air flow: 450 mL/min  
Data Rate: 20 Hz  
**Instrument** Agilent/HP6890 GC  
**Acknowledgement** Susan Forsyth - Walton County, FL - Tarball sample  
**Notes** Actual column length was calculated to be 15.7 m using holdup time and EZGC flow calculator (<http://www.restek.com/ezgc-mtfc>).